

Spezifikation

2track GL300W GPS-Tracker

Lieferumfang



- 2track GL300W GPS-Tracker
- Steckernetzteil 230V
- SIM-Karte ^[1]

Spezifikation

GSM/UMTS Spezifikation

Frequency:	GSM: 850/900/1800/1900 MHz UMTS: 850/1900/2100 MHz
Transmitting Power:	Class 4 (33dBm) for GSM 850 and EGSM Class 1 (30dBm) for DCS 1800 and PCS 1900 Class 3 (24dBm) for UMTS 850/1900/2100
GSM/GPRS Data Features:	GPRS: Support GPRS multi-slot class 12 (10 by default) Coding scheme: CS-1, CS-2, CS-3 and CS-4 Maximum of four Rx slots per frame
Transmission Data:	HSDPA R5: Max 3.6 Mbps (DL) WCDMA R99: Max 384 kbps (DL)/Max 384 kbps (UL) GPRS: Max 85.6 kbps (DL)/Max 85.6 kbps (UL)
HSDPA and WCDMA Features	HSDPA data rate corresponds with 3GPP R5. 3.6 Mbps on downlink WCDMA data rate corresponds with 3GPP R99/ R4. 384kbps on downlink and 384 kbps on uplink. Support both 16-QAM and QPSK modulation

GPS Spezifikation

GPS Chipset:	u-blox All-In-One GPS receiver
Sensitivity:	Autonomous: -147dBm, Hot start: -156 dBm, Reacquisition: -160 dBm Tracking: -162 dBm
Position Accuracy:	Autonomous: < 2.5m SBAS: < 2.0m
TTF (Open Sky):	Cold start: 27s average, Warm start: 27s average, Hot start: 1s average

Benutzer Interface

Power Button:	Power on and power off
Function Button:	For SOS alarm (not used)
UMTS/HSDPA and GSM Antennas:	Internal only
GPS Antenna:	Internal only
Indicator LED:	GSM, GPS and battery status
Mini USB Interface:	

Allgemeine Spezifikation

Dimension:	77.9mm * 39.9mm * 21.7mm
Weight:	72g
Internal Battery:	Li-Polymer 1700 mAh
Standby Time:	20 seconds reporting: ca. 16 hours; 5 minutes reporting: 180 hours; 10 minutes reporting: 220 hours
Operation Temp.:	-20°C - +55°C
Water Resistance:	IPX5 compliant
Charging Voltage:	5V DC

[1] Nur im Lieferumfang im Zusammenhang mit einem GPS-Live-Tracking Abo und bleibt Eigentum von 2track.ch

Optionales Zubehör



USB-Ladekabel für
Zigarettenanzünder 12V