

Spezifikation

2track G717-3G Plug'n'Play GPS-Tracker

Lieferumfang



- 2track G717-3G GPS-Tracker
- SIM-Karte ^[1]

Spezifikation

3G/GSM Spezifikation

Frequency:	3G: 900/2100 MHz GSM: 850/900/1800/1900 MHz
Data Support:	SMS, TCP, UDP
3G/GSM Antenna:	Internal Antenna for better security
CPU:	ARM Cortex M3 (32Bit)

GPS Spezifikation

GPS Chipset:	u-blox All-In-One GPS receiver, GPS and Glonass support
Tracking Sensitivity:	Autonomous: -147dBm, Hot start: -156 dBm, Reacquisition: -160 dBm Tracking: -162 dBm
Position Accuracy:	Autonomous: < 2.5m SBAS: < 2.0m
TTF (Open Sky):	Cold start: 27s average, Warm start: 27s average, Hot start: 1s average
GPS Antenna:	Internal Patch
Assist GPS:	Supported

Allgemeine Spezifikation

Dimension:	180mm * 32mm * 32mm
Weight:	50g (with Battery)
Internal Battery:	Li-Polymer 250 mAh
Power Consumption:	3mA 12V (Sleep), 33mA 12V (Power Save), 130mA 12V (Active Tracking)
Operation Temp.:	-10°C - +50°C
Water Resistance:	IPX5 compliant
Operating Voltage:	8-32V DC operational for 12V & 24V

[1] Nur im Lieferumfang im Zusammenhang mit einem GPS-Live-Tracking Abo und bleibt Eigentum von 2track.ch